

WHAT IS CLAIMED IS:

*Sub B<sup>1</sup>* 1. An information processing apparatus comprising:  
a motion detector for detecting a motion-related signal,  
which is information relating to motion, in accordance with  
an image signal; and  
a generator for generating a motion control signal in  
accordance with said motion-related signal.

2. An information processing apparatus according to  
claim 1, wherein said motion detector detects a motion  
vector as said motion-related signal.

3. An information processing apparatus according to  
claim 2, wherein said motion detector detects one motion  
vector for each block composed of a plurality of pixels at a  
predetermined position within a frame.

*Sub B<sup>2</sup>* 4. An information processing apparatus according to  
claim 2, wherein said generator generates, as said motion  
control signal, a horizontal component, a vertical component,  
a magnification component, and a rotation component in  
accordance with said motion vector.

5. An information processing apparatus according to

~~B/~~  
claim 1, further comprising a driving device for driving an object in accordance with said motion control signal.

*Sub B<sup>3</sup>* → 6. An information processing apparatus according to claim 5, wherein a chair is provided as said object, and said driving device comprises an actuator for moving said chair.

~~B/~~  
7. An information processing apparatus according to claim 6, further comprising a display device for displaying said image signal.

8. An information processing apparatus according to claim 1, wherein said motion control signal contains a plurality of components.

~~B/~~  
9. An information processing apparatus according to claim 1, wherein said motion detector detects said motion-related signal in accordance with a signal in a predetermined portion of the frame for said image signal.

*Sub B<sup>4</sup>* → 10. An information processing method comprising the steps of:

detecting a motion-related signal, which is information relating to motion, in accordance with an image signal; and

*B4*  
*Conel*  
generating a motion control signal in accordance with said motion-related signal.

11. An information processing method according to claim 10, wherein, in said motion detecting step, a motion vector is detected as said motion-related signal.

12. An information processing method according to claim 11, wherein, in said motion detecting step, one motion vector is detected for each block composed of a plurality of pixels at a predetermined position within a frame.

*Sub B5* → 13. An information processing method according to claim 11, wherein, in said generating step, as said motion control signal, a horizontal component, a vertical component, a magnification component, and a rotation component are detected in accordance with said motion vector.

14. An information processing method according to claim 10, further comprising a driving step for driving an object in accordance with said motion control signal.

*D1*  
15. An information processing method according to claim 10, wherein said motion control signal contains a plurality of components.

16. An information processing method according to claim 10, wherein, ~~in said motion detecting step, said motion-related signal is detected in accordance with a signal in a predetermined portion of the frame for said image signal.~~

*Sub B6* > 17. A storage medium storing a computer-controllable program, said program comprising the steps of:  
detecting a motion-related signal, which is information relating to motion, in accordance with an image signal; and  
generating a motion control signal in accordance with said motion-related signal.

18. A storage medium according to claim 17, wherein, in said motion detecting step, a motion vector is detected as said motion-related signal.

19. A storage medium according to claim 18, wherein, in said motion detecting step, one motion vector is detected for each block composed of a plurality of pixels at a predetermined position within a frame.

*Sub B7* > 20. A storage medium according to claim 18, wherein, in said generating step, as said motion control signal, a

B7  
cancel.

horizontal component, a vertical component, a magnification component, and a rotation component are detected in accordance with said motion vector.

21. A storage medium according to claim 17, said program further comprising a driving step for driving an object in accordance with said motion control signal.

22. A storage medium according to claim 17, wherein said motion control signal contains a plurality of components.

23. A storage medium according to claim 17, wherein, in said motion detecting step, said motion-related signal is detected in accordance with a signal in a predetermined portion of the frame for said image signal.